



NOTES:

1. PRE-CAST BOX, SEAT, AND LID SHALL BE CHRISTY CONCRETE PRODUCT MODEL G5 TRAFFIC VALVE BOX OR APPROVED EQUAL.
2. SURFACE OF LID SHALL BE LABELED "MONUMENT" ENGRAVED IN 1" HIGH LETTERS.
3. BRASS MARKER DISC SHALL BE ENGRAVED WITH RESPONSIBLE LICENSED SURVEYOR OR CIVIL ENGINEER REGISTRATION NO. AND MONUMENT POINT PUNCHED.
4. CONCRETE SHALL BE CLASS "A".
5. PLACE CONCRETE FOR MONUMENT IN DRILLED HOLE.
6. LOCKING GRADE RINGS (NOT SHOWN) SHALL BE INSTALLED WITH 3/8"x1" NC BOLT AND JAM NUT (IN 3 PLACES) WHEN STREET IS RESURFACED TO BRING MONUMENT LID FLUSH WITH NEW FINISHED GRADE.

LOCKING GRADE RINGS	
CHRISTY NO.	DESCRIPTION
G5GR10	1" HIGH CAST IRON
G5GR15	1-1/2" HIGH CAST IRON
G5GR20	2" HIGH CAST IRON



DRAWN BY: **M. LEE**
 CHECKED BY: **B. TRAN**
 APPROVED BY: **G. GOMEZ**
 DATE: **DECEMBER 2002**

MONUMENT

CITY OF SANTA CLARA

ST-15

PAGE: 15